

LCD-Digitalclock for large rooms and areas

C 90



C 90

42 cm wide
28 cm high
3 cm deep

New: Very flat and exclusive frontpanel design. The sanded Alunox material looks like satin-stainless-steel but leaves no fingerprints and is easy to clean.

Gapless digit segments for a better readability. The large 90 mm digits enable long reading distances for large rooms and floors. Therefore they are ideal for offices, conference rooms, receptions, etc.

All Segments have an excellent contrast for excellent readability also from wide viewing angles and during almost all lightning conditions. .

This clock can be installed wireless onto each wall. Easy, quick and cost-saving!

- Radio-controlled
- Wireless installation
- High contrast display
- Large and gapless digits for long reading distances
- Excellent readability even from wide viewing angles
- Symbols for radio signal reception, battery capacity etc.
- Menu guidance for manual operation
- Flat and modern design
- Battery life appr. 3 years
- Also available as installation kit
- Many options

A large clock for large rooms and floors. For reception areas, pharmacies, retail stores, offices, industry and many more.

C 90

Technical Specifications:

Radio reception: DCF-77
Quarz mode: +/- 0,1 seconds per day
Symbolic Representation: RF signal indication, battery capacity, menu guidance

Dimensions W x H x D: 423 x 283 x 25 mm
Front panel: Alunox (leaves no fingerprints)
Weight: 900 g
Digit height time: 90 mm
Reading distance normal: 8 m
Reading distance (max.): 35 m
Viewing angle (max.): 170°
Digit colour: black
Battery power: 4 pcs. 1,5 Volt AA
Battery life: appr. 3 years

Standard version:

Integrated radio receiver DCF-77
Automatic summer-/ wintertime changeover
Battery life appr. 3 years
Time representation hour / minutes

Options:

V - Mains operation 230 Volt
N - Secondary clock input with polarity change 12 to 60 Volt
E - External antenna with 6 m connection cable and plug
NTP- Network-Synchronisation
Air- AirTime Synchronisation
T - Temperature display internal (installed)
K - Temperature sensor external with appr. 6 m cable

The temperature can be shown alternatively with the date or fix.

This clock is also available as installation version without blind frame.
Do you have any questions? No problem! Please contact us.
We will be happy to provide you with help.

